



# TURCO<sup>®</sup> 6813

WATER-BASED ENVIRONMENTALLY ADVANTAGED PAINT REMOVER  
(US PATENT NOS. 5726140 & 5387363)

## DESCRIPTION:

TURCO 6813 is a viscous, light blue liquid formulated to remove multiple coats of paints, such as baked enamels, lacquers, varnish, synthetic enamels, zinc chromate primers, epoxies and polyurethanes.

TURCO 6813 paint remover clings to vertical as well as overhead surfaces and can be used on aluminum, magnesium, cadmium plated steels and other ferrous metals, including high strength steel.

## FEATURES:

TURCO 6813 paint remover offers these features:

1. NESHAP compliant
2. Meets corrosion requirements of MIL-R-29603
3. Nonflammable (per DOT definition)
4. Free of phenols, acids and chlorinated hydrocarbons
5. Readily rinses with cold water
6. Can be applied by non-atomizing spray, brush or flow-on methods

## USE INSTRUCTIONS:

**Application:** Apply by brush, non-atomizing spray or flow-on (no spray tip) methods to surface requiring stripping. Apply a smooth, even coat and allow sufficient dwell time (up to about 4 hours) for remover to penetrate and loosen paint. When paint is loosened, thoroughly agitate the surface with a stiff bristle brush. Reapply as necessary to remove any residual paint from more difficult to strip areas.

**Removal:** Spent TURCO 6813 and paint residues may be squeegeed off or rinsed with high pressure, high volume cold water. Brushing during rinsing operation assists in removal of all residues.

**NOTE:** TURCO 6813 may attack plastics, rubber seals and tires. These materials should be protected.

## DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to your TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

**CAUTION! May cause irritation to skin and eyes. May be harmful if swallowed.**

TURCO 6813 paint remover contains ammonium hydroxide. Do not spray in closed or confined areas. Use with adequate (equivalent to outdoor) ventilation. Avoid breathing of vapor for prolonged periods of time. Avoid contact with eyes, skin and clothing. Do not take internally.

Protective clothing, such as a chemical face shield or goggles and gloves, apron and boots, made from solvent resistant materials should be worn when handling this product.

Store this material in its original container in an area protected from direct exposure to the elements.

Store in closed containers away from excessive heat or direct sunlight.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

**NOTICE:**

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev.4/99(Sup.1/96)  
TDB #980