

TURCO[®] 5351 THIN

TANK TYPE EPOXY AND POLYURETHANE REMOVER

DESCRIPTION:

TURCO 5351 THIN is an amber, di-phase liquid developed to remove epoxy, polyurethane and other catalyzed finishes from ferrous and nonferrous surfaces.

TURCO 5351 THIN remover does not contain free acidic or alkaline constituents and is approved for use on high strength steels.

TURCO 5351 THIN should not be used on materials that are affected by chlorinated hydrocarbons.

FEATURES:

TURCO 5351 THIN offers these features:

1. Nonflammable
2. Used at ambient temperature
3. Used as received. No mixing or dilution required
4. Comes with built-in seal
5. Seal is maintained by addition of tap water
6. Freely rinses from parts with high pressure, high volume cold water

USE INSTRUCTIONS:

Tanks: Tanks and associated equipment may be fabricated from mild steel or stainless steel. Stainless steel is preferred.

Concentration: Use at full strength, as received.

Application: Immerse parts into stripper, below the seal layer. The seal layer retards evaporation of solvents and does not have stripping capabilities. Allow sufficient time for stripper to loosen finish.

Rinse: Remove parts from stripper tank and rinse with high volume, high pressure cold water.

Seal Maintenance: The seal layer is gradually depleted through evaporation and drag-out. Maintain seal layer at 10% by volume by addition of clean, cool water.

Stripper Control: Normal adjustments will require water only, but extended heavy use may also require additions of solvent. Refer to your TURCO Sales Engineer for specific recommendations.

DISPOSAL INFORMATION:

Dispose of spent stripper per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

DANGER!

TURCO 5351 THIN contains methylene chloride, phenol and sodium chromate. Avoid contact with eyes, skin and clothing. Do not take internally. Avoid prolonged breathing of vapors. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, apron and boots, made from solvent resistant materials should be worn when handling and using this product.

Containers exposed to moderate heat, above 32°C may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 6/99(Sup. 1/87)
TDB #321