



# TURCO® 6744

## NON-CHLORINATED PAINT AND SILICON REMOVER

### DESCRIPTION:

TURCO 6744 is a viscous light amber liquid product developed for stripping resistant primers and sealants, such as polysulfide primers and RTV and Silicoset silicone rubber. TURCO 6744 contains no HAP's and does not contain chlorinated solvents, phenols, chromates or salts of heavy metals. TURCO 6744 can be used on aluminum and ferrous alloys.

### FEATURES:

TURCO 6744 offers these features:

1. NESHAP compliant - contains no HAP's
2. Provides effective stripping of poly-sulfide primers
3. Low VOC vapor pressure (5 mm Hg)
4. Use at ambient temperature, above 15°C
5. Meets stock loss limits on aluminum established by major turbine engine manufacturers when tested in accordance with ARP 1755A

### HOW TO USE TURCO 6744 PAINT REMOVER:

**Application:** Apply a thick, uniform coating to surface being stripped by means of non-atomizing spray or brushing. Allow sufficient time for stripper to work. Agitation with a stiff bristle brush will aid in removal of finish.

**Rinsing:** Rinse with high volume, high-pressure cold water or steam.

### DISPOSAL INFORMATION:

Dispose of spent remover and paint residue per local, state and regional regulations. Refer to your TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

### CAUTION!

TURCO 6744 contains ingredients that may cause irritation. Avoid contact with eyes, skin and clothing. Do not take internally. Do not spray in confined areas. Avoid prolonged breathing of vapors. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing such as a chemical face shield or goggles and gloves, boots and apron made from solvent resistant neoprene should be worn and a respirator, with mechanical filter should be used for mist conditions.

Store containers at a temperature between 0°C to 50°C.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

**NOTICE:**

*The above information and recommendations concerning this product are based upon our laboratory tests and field use experience. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.*

Rev. 2/98(Sup. 10/90)  
TDB #99