



TURCO[®] 6869

LOW COMPOSITE VAPOR PRESSURE SOLVENT

DESCRIPTION:

TURCO 6869 is a water-white liquid formulated to replace methyl ethyl ketone and similar solvents that are environmentally unacceptable due to their high composite vapor pressure.

TURCO 6869 is ideal for hand-wipe cleaning of metal surfaces prior to painting or bonding, and for cleaning bearings, instruments and electronic components.

APPLICABLE SPECIFICATIONS:

TURCO 6869 meets the composite vapor pressure requirements prescribed by the Aircraft/Aerospace NESHAP and the South Coast Air Quality management District Rule 1124, "Aerospace Assembly and Component Coating Operations".

FEATURES:

TURCO 6869 offers these features:

1. Evaporates rapidly from surfaces.
2. Does not leave surface residue after evaporation.
3. Non-corrosive to all common aircraft alloys.
4. Excellent solvency for oily soils and paint and sealant residues.
4. Vapor pressure of 35 mm Hg.

USE INSTRUCTIONS:

TURCO 6869 is used at full strength. Apply to metal surfaces, using clean, absorbent cloths. Remove soil residue with clean cloth. Keep cloth saturated with TURCO 6869. Change cloth frequently for optimum results.

DISPOSAL INFORMATION:

Dispose of cloths and spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information. Store used cloths in sealed metal containers to avoid possibility of fire due to spontaneous combustion.

WARNING! Flammable! Harmful if swallowed.

TURCO 6869 contains aliphatic naphthas, including heptane, and methyl n-propyl ketone. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation. Avoid prolonged breathing of fumes.

Protective clothing such as a chemical face shield or goggles and gloves, apron and boots, made from solvent resistant materials should be worn when handling and using this product.

Do not use TURCO 6869 near open flames, cutting torches or welding arcs, since material has a Tag Closed Cup flash point of 20°F (-6°C).

Do not store containers above 120°F (49°C) or near strong oxidizing agents. Use care in opening drums to avoid spurting of contents.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

9/96 FG:00675
TDB #86-C