



Technical Information Bulletin

TURCO[®] SOLV

SOLVENT CLEANER

DESCRIPTION:

TURCO SOLV is a clear colorless solvent-based cleaner formulated for in-place of electrical equipment.

TURCO SOLV evaporates to complete dryness without leaving residues that can attract carbon dust, metallic particles or other contaminants that may damage electric equipment.

TURCO SOLV is also suitable for general maintenance cleaning of manufacturing, automotive, marine and transportation equipment. TURCO SOLV removes greases, lube oils, rust preventives, inks and hand marks from metallic as well as other surfaces. TURCO SOLV is not recommended for use on materials that are affected by chlorinated hydrocarbons.

FEATURES:

TURCO SOLV offers these features:

1. Meets the composite vapor pressure requirements of SCAQMD, Rule 1124 (<45 mm Hg)
2. Controlled evaporation, leaves no residue
3. Can be used on well-bonded paints
4. Will not corrode metals
5. Can be used on most electrical insulating materials
6. No flash at initial boiling (45°C).

USE INSTRUCTIONS:

Spray Applications: Spray as received from pressure pot or air suction gun @ 0.2 to 0.4 gallons per minute, with a 15° spray tip at a pressure of 15 to 30 psi. For in-place spray cleaning of diesel electric generators, remove car body filters for ventilation.

Wipe or Brush Applications: : Use clean, lint-free cotton cloth or solvent resistant brushes.

DISPOSAL INFORMATION:

Dispose of spent solvent and/or rags per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

WARNING! Causes irritation.

TURCO SOLV contains methylene chloride, trichloroethylene, aliphatic petroleum solvent and 2-butoxyethanol. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not

take internally. Do not spray in closed or confined areas. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron made from solvent resistant materials, should be worn when handling this product.

Containers exposed to moderate heat, above 30°C may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Do not use TURCO SOLV near welding arcs, torches and open flames, since hazardous gases may be formed. Rags used for application of TURCO SOLV may become combustible in time and should be stored in safety containers.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 8/99 (Sup. 12/86)
TDB #217-4