

TURCO[®] ALUMIFILM REMOVER L

DESCRIPTION:

TURCO ALUMIFILM REMOVER L is a clear blue viscous liquid formulated to remove TURCO ALUMIFILM temporary protective coating from aluminum and magnesium surfaces by spray, brushing or flow-on methods.

TURCO ALUMIFILM REMOVER L will not remove or stain chromate conversion coatings, chromic acid anodized or sulfuric acid anodized surfaces and is non-crazing to Plexiglas.

FEATURES:

TURCO ALUMIFILM REMOVER L offers these features:

1. Nonflammable
2. Non-corrosive to aluminum and magnesium
3. Clings to vertical and overhead surfaces
4. Applied by spraying, brushing and flow-on methods
5. Easily removed by water
6. Will not cause hydrogen embrittlement of high strength steel
7. Will not attack well bonded paints

USE INSTRUCTIONS:

Equipment: Spraying equipment may be fabricated from mild steel, aluminum or stainless steel. Stainless steel is preferred.

Application: Apply TURCO ALUMIFILM REMOVER L as received by pressure pot spraying equipment, brushing or flow-on methods. Allow sufficient dwell time for thorough loosening of the coating. Agitate areas with stiff bristle brush to speed loosening.

Rinsing: Remove coating and residue with high pressure cold water or with conventional steam cleaning. Slight brushing during rinse operation insures complete removal of all residues.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION!

TURCO ALUMIFILM REMOVER L contains 2-butoxyethanol and ethylene diamine. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron made from solvent resistant materials should be worn when handling and using this product. A respirator equipped with an organic vapor canister should be worn if TLV are exceeded

Transport and store in closed containers away from strong acids at temperature below 50°C.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 9/99(Sup. 5/90)
TDB #924