



TURCO[®] RUST BLOC

RUST INHIBITOR

DESCRIPTION:

TURCO RUST BLOC is an alkaline liquid used as a rust inhibiting rinse additive or cleaner. It provides temporary in-plant rust protection for steel and cast iron.

FEATURES:

TURCO RUST BLOC offers these features:

1. Approved to P&W SPMC 140, SPS 140
2. Used at low concentrations
3. Can be used at up to 200°F to promote flash drying
4. Low foam
5. Biodegradable
6. Long tank life
7. Free of chromate and nitrite
8. No toxic fumes or vapors
9. Free of oils, HAP's and VOC's

USE INSTRUCTIONS:

Tanks: Tanks and associated equipment should be fabricated from stainless steel.

Rinse Inhibitor: Make up at 0.7-1.0% by volume with good quality water. Use as final rinse to provide rust protection. Operate at ambient to 200°F.

Spray Washer: Make up at 2-5% by volume with good quality water. Operate at ambient to 200°F (85°C) with a spray pressure of 10-60 psi. Check periodically to insure all nozzels impinge on parts and no nozzles are plugged.

Agitated Dip: Make up at 10-20% by volume with good quality water. Operate at ambient to 200°F (85°C) with good mechanical agitation.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to your TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

WARNING! Causes eye irritation. May cause skin irritation.

TURCO RUST BLOC contains mildly alkaline materials. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Store in closed containers away from excessive heat or direct sunlight.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 4/97(Sup.11/96) FG: A03752
TDB #967