



TURCO[®] 5873 NC

NON-CHROMATED - NON-PHENOLIC PAINT REMOVER

Description

TURCO[®] 5873 NC is a viscous, amber, liquid paint remover formulated to remove multiple coats of paints, such as baked enamels, lacquers, varnishes, synthetic enamels, zinc chromate primers, epoxies and polyurethane.

TURCO[®] 5873 NC paint remover clings to vertical as well as overhead surfaces and can be used on aluminum, magnesium, cadmium plated steels as well as ferrous metals.

Features

TURCO[®] 5873 NC paint remover offers these features:

1. Non-flammable
2. Free of phenols and acid
3. Readily rinses with cold water
4. Can be applied by non-atomizing spray, brush or flow-on methods
5. Used as received. No mixing or dilution required
6. Passes hydrogen embrittlement test per ASTM F-519, type IC.
7. Listed in Douglas Process Material Index (DPM) #5649

Use instructions

Application: apply by brush, non-atomizing spray, or flow-on (no spray tip) methods to surface requiring stripping. Apply a smooth, even coat and allow sufficient dwell time for remover to penetrate and loosen paint. When paint is loosened, thoroughly agitate the surface with a stiff bristle brush. If paint adheres to specific areas, reapply TURCO[®] 5873 NC and allow additional dwell time before rinsing.

Rinsing: Rinse remover and paint residue with high pressure, high volume cold water or stream. Brushing during rinsing operation assists in removal of all residues.

NOTE: TURCO[®] 5873 NC will attack plastics, rubber seals and tires. These materials should be protected.

Disposal information

Dispose of spent remover and paint residue per local, state and regional regulations. Refer to your local TURCO territory manager, region sales office or TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

Caution

TURCO® 5873 NC paint remover contains chlorinated hydrocarbons and methanol. Do not spray in closed or confined areas without adequate protective precautions. Use with adequate (equivalent to outdoor) ventilation. Avoid breathing of vapor. Avoid contact with eyes, skin and clothing. Do not take internally. Protective clothing, such as a chemical face shield or goggles and gloves, apron and boots, made from solvent-resistant materials should be worn when handling this product.

Do not use TURCO® 5873 NC near welding arcs, torches and open flames, since hazardous gases may be formed.

Containers exposed to moderate heat, above 32°C (90°F), may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Refer to container label or TURCO MATERIAL SAFETY DATA SHEET for additional handling, precautionary and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Ref. 4/91 (Sup. 8/85)
F.G. #A3530