

TURCO® 5948 A

CONCENTRATED, HEAVY DUTY EXTERIOR AIRCRAFT CLEANER

DESCRIPTION

Turco 5948A is an alkaline, water base, concentrated compound formulated to effectively clean painted and unpainted aircraft exterior surfaces when diluted with water. Turco 5948A is ideally suited for use on all jets.

CHARACTERISTICS

Effectively removes dirt, petroleum and synthetic oil film, grease, carbon and exhaust stains from aircraft surfaces, landing gear, wheel wells, flaps, etc.

For use on all metals and well-bonded paint. Non-streaking and non-staining to aluminum. Non-crazing to Plexiglas. Conforms to Douglas C.S.D. #1 and ARP 1525 #2 and Boeing D-6-17487. Restores paint luster. Free rinsing properties blended into Turco 5948A eliminate the danger of paint streaking so often encountered in aircraft exterior surface cleaners.

USE INSTRUCTIONS

Heavy Duty and General Purpose Cleaning: Where accumulations of oil, grease, carbon and traffic soils are heavy, mix 1 part Turco 5948A with 9 parts water. Mix well and apply by spray or mop. Agitate surface with mops or soft bristle brushes and pressure rinse with clean tap water. Dilution may be extended dependent upon degree of soils.

Extremely Heavy Duty Cleaning: For extremely heavy accumulations of oils, grease, carbon and soils usually found on landing gears, wheel wells, flaps etc., a mixture of 1 part Turco 59 48A,

1 part water and 3 parts T 680Z is suggested. The solvent mixture will form a thick stable emulsion with agitation. Spray or mop the emulsion on the soiled areas, let dwell for a few minutes, agitate with a soft bristle brush and high pressure rinse with tap water.

Application

Apply the Turco 5948A solutions with either pressure pot or barrel pump using a #6504 spray nozzle or equivalent. Recommended spray pressure is 2- 3 atmospheres. Can also be applied with brush or mop.

Limitations

None. For use on painted surfaces and on all metals including high strength steels. (Tested per Douglas Stressed Ring Procedure.) Safe on Plexiglas if used with a non-crazing solvent.

Before using this product refer to container label and Turco Material Safety Data Sheet for additional precautionary, handling and first aid information.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to your TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

WARNING! On contact causes eye irritation. May cause skin irritation.

TURCO LIQUID SPRAYEZE NP-LT contains silicate and surfactant. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, made from alkaline resistant materials should be worn when handling this product.

Transport and store in closed containers at temperature below 55°C.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss damage or injury, direct or consequential, arising out of the use of this product.

Rev.0206 - X