



## TURCO<sup>®</sup> 6813-ED

### WATER-BASED ENVIRONMENTALLY ADVANTAGED PAINT REMOVER (US PATENT NRS. 5726140, 5821209 & 5851972)

#### DESCRIPTION:

TURCO 6813-ED is a viscous, blue-green liquid formulated to remove multiple coats of aircraft paints, such as epoxies and polyurethanes, including such resistant primers as Koroflex.

TURCO 6813-ED paint remover clings to vertical as well as overhead surfaces and can be used on aluminum, magnesium, cadmium plated steels and other ferrous metals.

#### FEATURES:

TURCO 6813-ED paint remover offers these features:

1. Meets requirements of TT-R-2918 (Long term storage test pending)
2. Passes ASTM F-519 Type 1A hydrogen embrittlement test
3. Stays active for many hours
4. Free of hazardous Air Pollutants (HAP's)
5. Nonflammable (per DOT definition)
6. Free of phenols, acids, methylene chloride and other chlorinated hydrocarbons and chrome or any other heavy metals
7. Readily rinses with cold water
8. Can be applied by non-atomizing spray, brush or flow-on methods

#### USE INSTRUCTIONS:

**Application:** Apply by brush, non-atomizing spray or flow-on (no spray tip) methods to surface requiring stripping. Apply a smooth, even coat and allow sufficient dwell time for remover to penetrate and loosen paint. A mist coat, followed by a light full, even coat is preferred. When paint is loosened, thoroughly agitate the surface with a stiff bristle brush. If paint adheres to specific areas, just allow additional dwell time before removing from surface. TURCO 6813-ED remains active for several hours so additional applications are often not required.

**Removal:** Spent TURCO 6813-ED and paint residues may be squeegeed off or rinsed with high pressure high volume cold water. Squeegeeing, followed by a wash with an alkaline cleaner is preferred. If reapplication is required, the stripped paint and spent remover should be squeegeed off and, without an intervening alkaline wash or water rinse, the second coat applied immediately before the surface can dry.

**NOTE:** TURCO 6813-ED may attack plastics, rubber seals and tires. These materials should be protected.

## **DISPOSAL INFORMATION:**

Dispose of spent solution per local, state and regional regulations. Refer to your TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

**CAUTION: May cause irritation to skin and eyes. May be harmful if swallowed.**

TURCO 6813-ED paint remover contains ammonium hydroxide. Do not spray in closed or confined areas. Use with adequate (equivalent to outdoor) ventilation. Avoid breathing of vapor for prolonged periods of time. Avoid contact with eyes, skin and clothing. Do not take internally.

Protective clothing, such as a chemical face shield or goggles and gloves, apron and boots, made from solvent resistant materials should be worn when handling this product.

Store in closed containers away from excessive heat or direct sunlight.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

## **NOTICE:**

*The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.*

Rev. 4/99(Sup. 9/98)  
TDB #242