



TURCO[®] 6864

LOW COMPOSITE VAPOR PRESSURE SOLVENT

DESCRIPTION:

TURCO 6864 is a water-white liquid formulated to replace methyl ethyl ketone and similar solvents that are environmentally unacceptable due to their high composite vapor pressures.

TURCO 6864 is ideal for hand-wipe cleaning of metal surfaces prior to painting or bonding.

APPLICABLE SPECIFICATIONS:

TURCO 6864 meets the composite vapor pressure requirements prescribed by the South Coast Air Quality Management District, Rule 1124 "Aerospace Assembly and Component Coating Operations" and the Aircraft/Aerospace NESHAP requirement for wipe solvents.

FEATURES:

TURCO 6864 offers these features:

1. NESHAP compliant
2. Boeing(McDonnell-Douglas) approved
3. Evaporates rapidly from surfaces
4. Does not leave surface residue after evaporation
5. Non-corrosive to most metals
6. Excellent solvency for oily soils, shop soils, and fingerprints
7. VOC Vapor pressure of 34 mm Hg

USE INSTRUCTIONS:

TURCO 6864 is used at full strength. Apply to metal surfaces using clean, absorbent cloths. Remove soil residue with clean cloth. Keep cloth saturated with TURCO 6864. Change cloth frequently for optimum results.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information. Store used cloths in sealed metal containers to avoid possibility of fire due to spontaneous combustion.

WARNING! Causes skin or eye irritation. Harmful if swallowed.

TURCO 6864 contains toluene, ester solvents, mixed ketones and isopropanol. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, made from solvent resistant materials should be worn when mixing and using this product.

Do not use TURCO 6864 near open flames, cutting torches or welding arcs, since material has a Tag Closed Cup flash point of -5°C.

Do not store containers above 50°C or near strong oxidizing agents. Use care in opening drums to avoid spurting of contents.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

New 4/98
TDB #180