

# **TURCO<sup>®</sup> 6880**

## **TEMPORARY PROTECTIVE COATING REMOVER**

### **DESCRIPTION:**

TURCO 6880 is a clear light amber viscous liquid formulated to remove TURCO 6846 temporary protective coating (or other alkaline removable coatings) from aircraft surfaces by spray, brushing or flow-on methods.

TURCO 6880 will not remove or stain chromate conversion coatings, chromic acid anodized or sulfuric acid anodized surfaces and is non-crazing to Plexiglas.

### **FEATURES:**

TURCO 6880 offers these features:

1. Rapidly attacks and liquefies alkaline removable coatings
2. Low (81 g/l) VOC, Zero HAP's
3. Nonflammable
4. Non-corrosive to aluminum and magnesium
5. Clings to vertical and overhead surfaces
6. Applied by spraying, brushing and flow-on methods
7. Easily removed by water
8. Safe for use on high strength steel
9. Safe on well bonded paints

### **USE INSTRUCTIONS:**

**Equipment:** Spraying equipment may be fabricated from mild steel, aluminum or stainless steel. Stainless steel is preferred.

**Application:** Apply TURCO 6880 as received, at ambient temperatures by pressure pot, spraying equipment, brushing or flow-on methods. Allow sufficient dwell time for thorough loosening of the coating. Agitate areas with stiff bristle brush to speed loosening.

**Rinsing:** Remove coating and residue with high pressure water or with conventional steam cleaning. Slight brushing during rinse operation insures complete removal of all residues.

## **DISPOSAL INFORMATION:**

Dispose of spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

## **CAUTION!**

TURCO 6880 contains organic solvents and amines. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, boots and apron made from neoprene should be worn by using personnel. A respirator equipped with an organic vapor canister should be worn if TLV is exceeded.

Transport and store in closed containers away from strong acids at temperatures below 120°F (49°C).

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

## **NOTICE:**

*The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.*

4/97  
TDB #312