



Technical Information Bulletin

Turco 6943
POLY SULFIDE SEALANT REMOVER

Description

TURCO 6943 is a clear liquid, developed specifically for removing poly sulfide sealants from fasteners or other tools in dip tank application. Also suitable for ultrasonic agitation.

Features

TURCO 6943 offers the following features:

1. Effective cleaning of fasteners polluted with poly sulfide sealants.
2. Flash point above 100°C.
3. Safe on all materials used in fasteners
4. Does not contain NMP, phenols, chromate or chlorinated solvents.

Use instructions

Equipment.

Process tank of mild steel with heating and agitation (can be ultra sonic), a lid with extraction system is recommended.

Process.

Typically, heat the tank to 45-55°C and immerse the fasteners for 30 minutes in the undiluted product. Agitation is advisable; the actual process specific parameters such as time, temperature and agitation type need to be determined according to the severity of pollution. In order to increase cleaning efficiency and effectiveness the temperature can be raised till 15°C below the flash point.

After removal from the tank, rinse using tap water prior to further processing.

Disposal information

Dispose of spent cleaner and residues per local, state and regional regulations.

Refer to your Turco Material Safety Data Sheet for additional disposal information.

Before using this product refer to container label and Turco Material Safety Data Sheet for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.