



TECHNICAL

DATA

BULLETIN NO.

386

TURCO PRODUCTS • A DIVISION OF TP INDUSTRIAL, INC. • A SUBSIDIARY OF PUREX INDUSTRIES, INC. • BOX 8200, CARSON, CALIFORNIA 90749
OFFICES IN ALL PRINCIPAL CITIES

TURCO® 1685 STEAM-PRESSURE CLEANER FOR REACTIVE METALS

DESCRIPTION:

TURCO® 1685 is a clear, amber, liquid compound designed for steam and high pressure water cleaning of reactive metals, automotive equipment, trailers, aircraft, machinery and industrial plant equipment. TURCO 1685 is free of soaps, resins and oils. The emulsifying agents used in TURCO 1685 enable oils, grease and bonded dirt to be readily and freely rinsed away, without the use of agents that produce disagreeable fumes or objectionable odors.

BENEFITS:

TURCO 1685 offers these benefits:

1. Concentrate is readily soluble in tap water at recommended concentrations.
2. Stable at all concentrations – no separation.
3. Nonflammable in concentrated or solution form.
4. Free rinsing, even with cold water.
5. Economical to use.
6. Free of soaps, resins and chlorinated solvents.

USE INSTRUCTIONS:

Steam Cleaner: Add 1 gallon of TURCO 1685 to 40 to 50 gallons of water. Mix well. Flow of concentrate can be adjusted according to the cleaning requirements of each job. Keep steam nozzle at least 12 inches from painted surfaces to prevent heat damage to paint. Rinse with warm or cold water.

High Pressure Water Cleaning: Add 1 gallon of TURCO 1685 to 30 to 40 gallons of water. Adjust flow according to the cleaning requirements of each job. Rinse with warm or cold water.

Note: Turco 1685 is not recommended for use on electrical equipment, unless equipment is protected.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to your local TURCO Territory Manager, District Sales Office, OSHA FORM 20 SHEET or TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION:

TURCO® 1685 contains silicate. Avoid contact with eyes, skin and clothing. Do not take internally. Do not spray in enclosed or confined areas. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron, made from alkaline resistant neoprene, should be worn when using and handling this product.

Store and ship in closed containers away from excessive heat, above 130°F, or direct sunlight.

Refer to container label, TURCO MATERIAL SAFETY DATA SHEET or OSHA FORM 20 SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.