



## **TURCO<sup>®</sup> 5770**

### **MULTI-PURPOSE OIL COMPOUND**

#### **DESCRIPTION:**

TURCO 5770 is a pale straw colored, slightly viscous, liquid compound originally intended for use as a seal additive for TURCO 5555B. It has also been found to be a very effective de-watering oil for critical metal components such as engine bearings.

#### **FEATURES:**

TURCO 5770 offers these features:

1. Supplied in ready to use liquid form
2. Can be used on all metals
3. Typical minimum flash point, 130°C COC
4. Contains no chlorinated hydrocarbons, phenols, chromates or heavy metals
5. Multi purpose use reduces stocking requirements

#### **USE INSTRUCTIONS:**

1. When used as a seal additive for TURCO 5555-B, add to the working bath to maintain a seal of 10 to 12 percent of the total volume or a minimum of 4".
2. When used as a de-watering oil, use as received at 100° to 110°C. Immerse clean metals parts for 5 to 10 minutes to vaporize any trapped water.

**Removal:** TURCO 5570 can be removed by alkaline, emulsion and solvent cleaners. Consult your TURCO Sales Engineer for the best remover based upon production needs.

#### **DISPOSAL INFORMATION:**

Dispose of spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

#### **WARNING! Contact may cause skin or eye irritation.**

TURCO 5570 contains petroleum distillates. Avoid contact with eyes, skin and clothing or prolonged breathing of vapor. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing such as a chemical face shield or goggles and gloves, made from solvent resistant materials should be worn when using and handling this product

Transport and store in closed container at temperatures between 0° to 50°C.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

**NOTICE:**

*The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with these or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.*

Rev. 10/99 (Sup.10/92)  
TDB #32