



# TURCO<sup>®</sup> 5948 DPM

## CONCENTRATED, HEAVY DUTY CLEANER

### DESCRIPTION:

TURCO 5948 DPM is an alkaline, water base, blue concentrated compound formulated to effectively clean painted and unpainted aircraft exterior and interior surfaces when diluted with water. TURCO 5948 DPM is ideally suited for use on all models of jet aircraft. TURCO 5948 DPM is also designed to be used in immersion tanks, for dip applications.

### FEATURES:

TURCO 5948 DPM offers these features:

1. Approved by Pratt & Whitney as SPMC 105 for SPOPs 1, 208 & 209
2. Conforms to McDonnell Douglas C.S.D. #1
3. Effectively removes jet soils, such as synthetic oil films, grease, carbon and exhaust residues from aircraft exterior surfaces, landing gears, wheel wells, flaps, etc.
4. For use on all aircraft metals and well bonded paint
5. Nonstaining and nonstreaking to aluminum
6. Noncrazing to Plexiglas
7. Readily soluble and stable in water mixtures
8. Restores paint luster
9. Free rinsing
10. Ideal for exterior and interior cleaning, as well as parts cleaning
11. Pleasant and refreshing odor
12. Nonflammable
13. Does not contain phosphates, chromates or butyl cellosolve
14. Will not attack asphalt ramps

### USE INSTRUCTIONS:

- 1) **HEAVY DUTY AND GENERAL PURPOSE CLEANING:** Where accumulations of oil, grease carbon and traffic soils are heavy, mix 1 part Turco 5948 DPM with up to 9 parts water. Mix well and apply by spray or mop. Spraying may be accomplished with a TURCO Barrel Pump or Sprayer. Agitate surface with mops or soft bristle brushes and pressure rinse with clean tap water. Dilution may be extended dependent upon degree of soils.
  - a) For light soils the product may be extended with up to 30 parts water.
  - b) For use in foam generators, dilute 1 part cleaner with 10 to 20 parts water.

- c) For interior cleaning TURCO 5948 DPM may be diluted 1 part cleaner with 50 to 100 parts water.
- 2) **IMMERSION CLEANING:** TURCO 5948 DPM may be diluted 1 part cleaner with 3 to 20 parts water, depending on soil load. Use at 65° to 80°C for 5 to 15 minutes. Ideal for ultrasonic tanks.

## **DISPOSAL INFORMATION:**

Dispose of TURCO 5948 DPM per local, state and regional regulations. Refer to your TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

### **WARNING! Causes eye irritation. May cause skin irritation.**

TURCO 5948 DPM contains ethanolamine. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron, made from alkali-resistant materials, should be worn when handling and using this product.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

### **NOTICE:**

*The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage or injury, direct or consequential, arising out of the use of this product.*

Rev. 12/97 (Sup.7/96) FG: 03196  
TDB #89