



TURCO[®] 6037

NEUTRAL REMOVER FOR EPOXY AND POLYURETHANE COATINGS

DESCRIPTION:

TURCO 6037 is a yellow, viscous paint remover developed to remove epoxy, polyurethane and similar coatings from metal surfaces at room temperature.

TURCO 6037 remover clings to vertical surfaces and forms a surface film that helps retard evaporation and extends the working life of the stripper. TURCO 6037 should not be used on materials that are affected by chlorinated hydrocarbons.

FEATURES:

TURCO 6037 offers these features:

1. Conforms to MIL-R-81294B and is listed on QPL
2. Can be used on high strength steel
3. Nonflammable
4. Used as received, no mixing or dilution required
5. Applied by non-atomizing spray, brushing or flow-on methods
6. Rinsed from surfaces by high pressure cold water
7. Chemically neutral

HOW TO USE TURCO 6037 REMOVER:

Apply a thick coating by means of a non-atomizing spray, flow-on or by brushing. Allow sufficient time for remover to thoroughly loosen paint. When paint is loose, agitate all areas with a stiff bristle brush to insure complete removal of all paint.

Rinse TURCO 6037 and paint residue with high pressure, high volume cold water or with steam. Slight brushing during rinsing aids in complete removal of all residues.

Temperature: Room temperature is optimum. Product can be applied at lower or higher temperatures, but at reduced efficiency.

DISPOSAL INFORMATION:

Dispose of remover and paint residue per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION!

TURCO 6037 contains chlorinated hydrocarbons, phenol and chromate. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation. Avoid breathing vapors.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron made from solvent resistant materials should be worn when handling this product.

Do not use TURCO 6037 near welding arcs, torches and open flames, since hazardous gases may be formed.

Containers exposed to moderate heat, above 30°C, may develop sufficient internal pressure to rupture. Use care in opening containers to avoid spurting.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 9/99(Sup. 7/83)
TDB #203