



TURCO[®] 6226

NONCHLORINATED CLEANING SOLVENT

DESCRIPTION:

TURCO 6226 is a water-white liquid formulated for in-place cleaning of electric motors, generators, and similar electrical equipment. TURCO 6226 has also been found to be an excellent solvent for final wipe-down of aircraft clad skins after polishing.

TURCO 6226 evaporates to complete dryness without leaving residues that can pick up carbon dust, metallic particles or other contaminating soils after cleaning.

Although TURCO 6226 is free of chlorinated solvents, it can be used in-place of chlorinated solvents in many wipe-on, wipe-off applications.

FEATURES:

TURCO 6226 offers these features:

1. NESHAP compliant for wipe solvent applications
2. Controlled evaporation rate
3. Can be applied by pressure spray or hand-wipe methods
4. Non-corrosive to ferrous and nonferrous metals
5. Free of chlorinated solvents
6. Flash point of 50°C, Tag Closed Cup Method
7. Does not require post rinsing
8. Vapor pressure: 1 mm Hg at 20°C

USE INSTRUCTIONS:

Spray Method: Apply undiluted TURCO 6226 by means of pressure pot or drum pump. Ideal delivery has been found to be from 0.2 to 0.4 gallons per minute with a pressure of 30 psi. Do not atomize. For in-place cleaning of large generators such as the main generators of a diesel locomotive, remove car body filters to allow ventilation. Do not rinse.

Hand-Wipe Method: Apply undiluted TURCO 6226 to clean cloth. Wipe area to be cleaned. Keep cloth saturated with cleaner, change cloth frequently to avoid recontamination.

DISPOSAL INFORMATION:

Dispose of soiled rags in approved safety container per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

WARNING! Causes eye irritation. May cause skin irritation

TURCO 6226 contains aliphatic hydrocarbons. Avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron made from solvent resistant materials should be worn especially when spraying this product. Do not spray in closed or confined areas.

TURCO 6226 has a flash point of 50°C, Tag Closed Cup Method. Do not spray near open flames, welding arcs, cutting torches or other sources of ignition.

Store in closed containers away from excessive heat or direct sunlight.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 11/99(Sup.7/99)
TDB #933