



TURCO[®] 6709

LOW VOC VAPOR PRESSURE SOLVENT

DESCRIPTION:

TURCO 6709 is a water-white liquid formulated to replace ketones and chlorinated hydrocarbon solvents that are environmentally unacceptable.

TURCO 6709 is ideal for hand-wipe cleaning of metal surfaces prior to painting or bonding and for cleaning bearings, instruments and electronic components.

TURCO 6709 will remove paint stripping residues left on the surface when the stripper is squeegeed off rather than water rinsed. TURCO 6709 will also remove felt tipped pen inks and mill markings.

FEATURES:

TURCO 6709 offers these features:

1. NESHAP compliant, contains no HAP's
2. Flash point of 45°C, TCC method
3. Contains no ethylene glycol ethers; not reportable per SARA
4. VOC Vapor pressure of less than 4 mm Hg @ 20°C
5. Excellent solvency for inks and paint residues
6. Non-corrosive to ferrous and nonferrous metals
7. Evaporates completely from surface

USE INSTRUCTIONS:

TURCO 6709 is used at full strength. Apply to metal surfaces using clean, absorbent cloths. Keep cloth saturated with TURCO 6709. Remove soil residue with clean cloth. Change cloth frequently for optimum results. Collect contaminated cloths in sealed metal containers to avoid possibility of spontaneous combustion.

DISPOSAL INFORMATION:

Dispose of spent solution per local, state and regional regulations. Refer to TURCO MATERIAL SAFETY DATA SHEET for additional disposal information.

WARNING! Combustible! Harmful if swallowed.

TURCO 6709 is relatively non-hazardous when used as directed. As in the case of any chemical compound avoid contact with eyes, skin and clothing. Do not take internally. Use with adequate (equivalent to outdoor) ventilation. Avoid prolonged breathing of fumes.

Protective clothing, such as a chemical face shield or goggles, gloves, boots and apron made from solvent resistant materials should be worn when handling and using this product.

Do not use TURCO 6709 near open flames, cutting torches or welding arcs, since material is combustible.

Do not store containers above 50°C or near strong oxidizing agents. Use care in opening drums to avoid spurting of contents.

Before using this product refer to container label and TURCO MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

Rev. 10/99(Sup.10/91)
TDB #934