

Technical Information Bulletin

TURCO® 6930

ENVIRONMENTALLY ADVANTAGED HYDROGEN PEROXIDE ACTIVATED PAINT REMOVER (US PATENT No. 5821209)

DESCRIPTION:

TURCO 6930 is a low odour, thixotropic paint remover activated by hydrogen peroxide. It was developed for effective stripping of such resistant finishes as epoxies, epoxy primers, polyurethane, and similar catalysed aircraft paints.

TURCO 6930 paint remover offers a significant advance in paint stripper technology. It complies fully with the aircraft/aerospace NESHAP.

TURCO 6930 can be used on aluminium, mild steel, high strength steel, and titanium when used as directed. TURCO 6930 is not recommended for use on magnesium. TURCO 6930 meets the corrosivity requirements of TT-R-2918 except magnesium and cadmium.

FEATURES:

TURCO 6930 offers these features:

1. Low odour
2. Faster stripping
3. Safe on titanium and high strength steel
4. NESHAP compliant, 0 g/l H.A.P.S.; <2 mm Hg V.O.C. Vapour Pressure
5. V.O.C. 647 g/l
6. Significantly lower waste disposal costs
7. Can be easily treated on site (see MSDS)
8. Excellent cling to vertical and overhead surfaces

USE INSTRUCTIONS:

APPLICATION:

Apply a uniform coating to surface being stripped by means of non-atomising spray. Allow sufficient time for stripper to work. Performance improves as temperature increases. Agitation with a stiff bristle brush will aid in removal of the finish. Repeat if necessary.

REMOVAL:

Squeegee off bulk of loosened paint and TURCO 6930, followed by high-pressure water rinse.

DISPOSAL INFORMATION:

Dispose of spent remover and paint residue per local, state and regional regulations. Refer to HENKEL SURFACE TECHNOLOGIES MATERIAL SAFETY DATA SHEET for additional disposal information.

CAUTION!

TURCO 6930 contains hydrogen peroxide. Avoid contact with eyes, skin and clothing. Do not take internally. Do not spray in confined areas. Avoid prolonged breathing of vapours. Use with adequate (equivalent to outdoor) ventilation.

Protective clothing, such as a chemical face shield or goggles and gloves, should be worn and a NIOSH-approved respirator equipped with a mechanical filter should be worn for mist conditions.

Store containers at a temperature between 2°C and 35°C.

Before using this product refer to container label and HENKEL SURFACE TECHNOLOGIES MATERIAL SAFETY DATA SHEET for additional precautionary, handling and first aid information.

NOTICE:

The above information and recommendations concerning this product are based upon our laboratory tests and field use experience with this or similar products. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without warranty, express or

implied. Manufacturer's and seller's sole obligation shall be to replace that portion of the product shown to be defective. Neither shall be liable for any loss, damage, or injury, direct or consequential, arising out of the use of this product.

"The information presented herein is our interpretation of certain test results and field experience to date. This information is not to be taken as warranty or representation for which we assume legal responsibility, nor as permission or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation and verification."

© Henkel Corporation.